

Product Information

ISO Class 5 - 8

Cleanroom Class 100 – 100,000 EU Grade B/C/D USP <797>

SatPax® 570

Pre-wetted 55% Cellulose / 45% Polyester Nonwoven Cleanroom Wiper

SatPax® 570 combines Durx® 570 nonwoven wipers composed of a hydroentangled nonwoven blend of 55% cellulose and 45% polyester with a saturation level of 70% IPA and 30% DI water.

This pre-wetted format provides a cost effective and easy to use solution versus traditional bulk handling of solvents, maintenance of squirt bottles and inconsistent wetting and cleaning associated with wetting a dry wiper.



Other Class 5 and above Pre-wetted wipers

- SatPax® 670-R
- SatPax® 550

Key Attributes

- 55% cellulose / 45% polyester hydroentangled nonwoven blend
- No chemical binders in base material
- Pre-wetted with consistent 70% IPA/ 30% DI Water to a saturation level of 45%
- Re-sealable solvent resistant packaging
- · Wipers in c-folded configuration for single withdrawal

Benefits

- · Low extractables and fiber and particle counts
- Smooth and durable with good wet strength
- Reduces alcohol usage and preparation / handling costs
- Increases cleaning efficiency
- · Increases cleaning protocol consistency

Environmental

- Reduces VOC (Volatile Organic Compound) emissions
- · Complies with RoHS
- · Registered under REACH

Applications

- Designed for use in ISO Class 5 and higher cleanroom environments and USP <797> applications.
- Designed for use in wet cleaning of critical surfaces where control of flammable solvents and flammable solvent concentrations is required
- Final cleaning of surfaces or products prior to manufacturing or packaging
- High saturation level is ideal for removing cleaning and disinfecting residues in regulated environments

Alcohol Mixtures

Alcohol / DI Water mixtures can be varied to fit the customer requirements. Typical mixtures are 70/30 and 9/91 IPA/DI Water.

Saturation Levels

The amount of solution contained in each wiper can be varied according to customer requirements. Higher saturation levels apply more solution to the surface during cleaning.

www.berkshire.com

Contact: Tel 1 800 242 7000 / 1 413 528 2602

Americas	Tel 1 413 528 2602	Fax 1 413 528 2614	info@berkshire.com
Europe	Tel 44 (0) 870 757 2877	Fax 44 (0) 870 757 2878	enquiries@berkshire.uk.com
SE Asia	Tel 65 6252 4313	Fax 65 6252 4312	enquiries@berkshire.com.sg
Japan	Tel 81 3 5827 2380	Fax 81 3 5827 2382	master@berkshire.co.jp



Technical Data (In Dry State)

Attribute		Units	Value	Test Method
Basis Weight		g/m²	54.6	TAPPI T-410
Caliper		μm	245	TAPPI T-411
Fibers	<u>></u> 100µm	fibers/cm ²	210	IEST-RP-CC004.3, Sec 6.1.3 / Sec 6.2.2
Particles	<u>></u> 0.5µm	x10 ³ /cm ²	11	IEST-RP-CC004.3, Sec 6.1.3 / Sec 6.2.1
Sorbency	Capacity	mL/m²	296	IEST-RP-CC004.3, Sec 8.1 modified / Sec 8.2 modified
	Efficiency	mL/g	5.4	
	Rate	seconds	2	
Non-Volatile Residue	DI Water	g/m²	0.022	IEST-RP-CC004.3, Sec 7.1.2
	IPA	g/m²	0.0036	
Ions	Na ⁺	ppm	110	IEST-RP-CC004.3, Sec 7.2.2
	K ⁺	ppm	7.6	
	Ca ⁺⁺	ppm	8.7	
	Mg ⁺⁺	ppm	2.3	
	CI-	ppm	57	

Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
- Third party testing can be performed upon request

Order Information:

Product	Number	Size	Shts/pk	Pks/cs	IPA/DI	Saturation	Voc %Weight	Style
SatPax® 570	SPX570.001.24	7x8" (18x20cm)	90	24	70/30	45%	41.9%	C-fold

Other Berkshire Products



Wipers



Glove Liners



Mop Systems



Documentation Systems



Face Masks



Swabs